

ADVANCED TECHNICAL GROUP

Four Ports Antenna Simulator for TCAS Systems



Input:

Frequency: 1030/1090 MHz Input Connector Type: N Impedance: 50 Ohms Input Power: 54 dbm Pulse Width: 32 uSec

Duty Cycle: 1%

DC Port Resistance:

Fixed to one OEM configuration

Factory reconfigurable

Coupled Ports (Optional):

Connector Type: SMA Impedance: 50 Ohms

Coupling: 10-50 db available

ATG's Antenna Simulator provides the proper loading to OEM's TCAS Systems and allows testing without having to transmit into an antenna or expensive test equipment. The rear of the box provides optional coupled ports for each of the input ports.



Dimensions:

(LxWxH) 7.25 x 7.5 x 2.5 inches

Weight: 2.5 lbs.

Eight Ports Simulator Option (Top & Bottom)

An Antenna Simulator with 8 ports in a single housing is available for loading/testing of the top and bottom antenna ports simultaneously. Dimensions: (LxWxH) 9 x 8 x 3.25 inches. Weight 3 lbs.

14046 NW 82 Avenue Miami Lakes, Florida 33016

Phone: (305) 556-1957 FAX: (305) 556-6510 ISO 9001:2008 Certified

www.a-tg.com