



T1200B

ARINC 429 CONTROL DISPLAY UNIT

The one test set that covers the entire spectrum of the avionics industry



External 12 inch touch-screen display allows main unit to be located away from operation

- PS-2 style mouse may be used with or without touch-screen
- May be ordered with front or rear display connectors
- Easy-to-use menu selection of avionics test formats
- Test formats that follow specific OEM avionics CMM's
- Up to 10 words transmitted on each channel
- Transmission and reception of all ARINC 429 words
- Ability to decode VOR, ILS, ADF, VHF, HF, DME, LRA, and ATC associated words as well as all other BCD and BNR data words into easily recognizable engineering units
- Two low speed and two high speed ARINC 429 transmitter/receiver cards

The venerable T1200, a mainstay in avionics' shops worldwide, has been upgraded to extend its reliability and service life. The display has been replaced by a more reliable, external, touch sensitive color Liquid Crystal Display (LCD). Any system utilizing the ARINC 429 databus can be served with the universal T1200B CDU (Control Display Unit). The result is an unprecedented level of equipment compatibility - from on-board systems all the way through bench testing and sub-component applications.

A touch is all it takes. The "User Configuration" menu permits user selection of data to be transmitted or display of data received.

The T1200B CDU also offers these advantages:

- ARINC 429 Avionics Systems. With appropriate optional interface panels, it is compatible with all major makes of navigation / communication equipment.
- On-board Electrical Systems. This includes control and display functions such as operating or directional lights, electrical switching and cockpit display panels, etc.

GENERAL SPECIFICATIONS

RECEIVER OPERATION

Low Speed

Meets or exceeds ARINC 429 specifications

Bit Rate

25 KBPS maximum

Word Rate

0.5 to 400 words per second

High Speed

Meets or exceeds ARINC 429 specifications

Bit Rate

150 KBPS maximum

Word Rate

0.5 to 400 words per second

TRANSMITTER OPERATION

Low Speed

Meets or exceeds ARINC 429 specifications

Bit Rate

8.1 to 20.4 KBPS in 9 steps

Accuracy

$\pm 1\mu s$

Word Rate

5 to 32,000 ms in 1.0 ms increments

Accuracy

± 0.5 ms

Max. Word Rate

300 words per second

High Speed

Meets or exceeds ARINC 429 specifications

Bit Rate

80/100/125 KBPS

Accuracy

$\pm 1\mu s$

Word Rate

5 to 32,000 ms in 1.0 ms increments

Accuracy

± 0.5 ms

Max. Word Rate

1500 words per second

PHYSICAL CHARACTERISTICS

MAIN UNIT

Weight

18 lbs. (8.16 kg)

Size

7.0"H x 19.0"W x 16.0"D (rack mount)
(17.8 cm x 48.25 cm x 40.6 cm)

Power Requirements

50-60 Hz, 100-240 VAC

DISPLAY (W/ RESISTIVE TOUCH SCREEN)

Weight

7.5 lbs. (3.4 kg)

Size

12.2"H x 12.3"W x 5.7"D
(31 cm x 31.25 cm x 14.5 cm)

Power Requirements

50-60 Hz, 100-240 VAC



**14046 NW 82 Avenue
Miami Lakes, Florida 33016
Phone: (305)556-1957
FAX: (305) 556-6510**

**ISO 9001:2008
Certified**

www.a-tg.com

VERSIONS, OPTIONS, AND ACCESSORIES

When ordering please quote the full ordering number information.

Ordering Number	Version
90670	T1200B ARINC 429 Control Display Unit (110 V)
934	T1200B-RC ARINC 429 Control Display Unit -Rear Display Connectors (110 V)

Units come standard with two low speed and two high speed TX and RX ports

Discrete Function Interface Units (DFIU)

935	T1201 ADF/VOLR/MB/ILS/Thomson MMR DFIU
936	T1202 HF/VHF DFIU
937	T1203 DME/XPDR/LRA DFIU
938	T1204 RDMI/RMI//DDI/RAI DFIU
939	T1205A Control Head DFIU
941	T1207 GPS/MLS DFIU

T1200 DFIU cables and overlays are dependent upon unit under test (UUT). Contact Aeroflex for availability.

Standard Accessories

75610	Manual Operations, T1200B CDU
29972	Power Cord, 3 cord 125u 10a
58283	Cable DFIU T1200

Optional Accessories

89815	AC501200B5 Monitor Support Bracket
-------	------------------------------------

Used to mount display on front of the T1200B for rack mounted systems

30074	Power Cord EUR 10a 230 V
-------	--------------------------

Extended Warranty

87313	WT1200B/203C Extended standard warranty 36 months with scheduled calibration
87314	WT1200B/205C Extended standard warranty 60 months with scheduled calibration



**14046 NW 82 Avenue
Miami Lakes, Florida 33016
Phone: (305)556-1957
FAX: (305) 556-6510**

**ISO 9001:2008
Certified
www.a-tg.com**